



● TL2000-02



● TL2000-02U



● TL4000-04



● TL4000-06

#### Air Lubricator:

It adopts balanced inlet with relief device. With the advantages of stable pressure, high precision, quick reaction and firm lockup, can be freely combined with other air-source treatment products.

#### ■ Graphics Sign



#### ● Ordering Code



Series



Type  
2000  
3000  
4000  
5000



Pipe Size  
01: G1/8  
02: G1/4  
03: G3/8  
04: G1/2  
06: G3/4  
10: G1




Iron Shell  
No Mark;  
2000 No Iron Shell  
3000-5000 With Iron Shell  
U, 2000 With Iron Shell

#### ■ Technical Parameter


| Specification               | TL2000-02/01          | TL3000-03/02      | TL4000-04/03       | TL4000-06 | TL5000-10/06 |
|-----------------------------|-----------------------|-------------------|--------------------|-----------|--------------|
| Applicable Medium           | Air                   |                   |                    |           |              |
| Rating Flow(L/min)          | 800                   | 1700              | 5000               | 6300      | 7000         |
| Max Pressure                | 1.0MPa                |                   |                    |           |              |
| Applicable Temperature      | 0-60°C                |                   |                    |           |              |
| Recommended Lubricating Oil | ISOVG32 or Equivalent |                   |                    |           |              |
| Gauge Port Size             | G1/8                  |                   | G1/4               |           |              |
| Min. Flow For Oil Drip      | 15L/min               | 30L/min           | 50L/min            | 50L/min   | 190L/min     |
| Lubricating Oil Capacity    | 25CM <sup>3</sup>     | 50CM <sup>3</sup> | 130CM <sup>3</sup> |           |              |

#### ■ Figure Dimension


● TL2000-02/01



● TL3000-03/02 TL4000-04/03 TL4000-06



● TL5000-10/06



| Type         | A  | B   | C  | D  | E  | F    | G    | H   | I  | J  | M   |
|--------------|----|-----|----|----|----|------|------|-----|----|----|-----|
| TL2000-02/01 | 40 | 122 | 38 | 40 | 27 | 8.4  | G1/4 | 5.4 | 30 | 22 | 2.3 |
| TL3000-03/02 | 53 | 142 | 38 | 53 | 40 | 8    | G3/8 | 6.5 | 41 | 23 | 2.3 |
| TL4000-04/03 | 70 | 177 | 41 | 70 | 54 | 10.5 | G1/2 | 8.5 | 50 | 26 | 2.3 |
| TL4000-06    | 70 | 177 | 41 | 70 | 54 | 10.5 | G3/4 | 8.5 | 50 | 26 | 2.3 |
| TL5000-10/06 | 90 | 254 | 45 | 90 | 66 | 13   | G1   | 11  | 70 | 35 | 3.2 |