

TF Series Filter

■ Graphics Sign



Air Filter:

It is mainly used for cleaning and effectively eliminates various impurities in the compressed air from compressors with automatic discharge structure, long service life, higher safety. There are multiple specifications for your choice.

● Ordering Code

TF	2000	02	D	U
Series	Type	Pipe Size	Drainage Type	Iron Shell
	2000 3000 4000 5000	01: G1/8 02: G1/4 03: G3/8 04: G1/2 06: G3/4 10: G1	No Mark; Standard Manual Drain Type D, Auto Drain	No Mark; 2000 No Iron Shell 3000-5000 With Iron Shell U, 2000 With Iron Shell




■ Technical Parameter


Specification	TF2000-02/01	TF3000-03/02	TF4000-04/03	TF4000-06	TF5000-10/06
Applicable Medium	Air				
Rating Flow(L/min)	750	1500	4000	6000	7000
Filtration	5 μm				
Max Pressure	1.0MPa				
Applicable Temperature	0~60°C				
Gauge Port Size	G1/8		G1/4		
Drain Holding Capacity	15CM ³	20CM ³	45CM ³		130CM ³

■ Figure Dimension


● TF2000-02/01



● TF3000-03/02 TF4000-04/03
TF4000-06 TF4000-10/06



● TF3000-03D/02D TF4000-04D/03D
TF4000-06D TF4000-10D06D



Type	A	B	C	D	E	F	G	H	I	J	K	N	Auto Drain
													B
TF2000-02/01	40	135	27	8.4	5.4	17	G1/4	11	40	30	30	2.3	135
TF3000-03/02	53	132	40	8	6.5	17	G3/8	14	53	41	41	2.3	187
TF4000-04/03	70	168	54	10	8.5	17	G1/2	18	70	50	50	2.3	223
TF4000-06	70	168	54	10	8.5	17	G3/4	18	70	50	50	2.3	227
TF5000-10/06	90	248	56	13	11	23	G1	24	90	70	70	3.2	302